



Washbasin	Dimension	Weight	Order number
with overflow, with tap platform, underneat	h glazed, 650 mm		
Colors			
00 White Alpin			
Variant			
•	650 x 440 mm	19.600 kilogram	2366650000
⊠	650 x 440 mm	19.600 kilogram	2366650060
Accessory			
Accessory			
Design Siphon		1.500 kilogram	005036
Suitable products			
Siphon cover for # 236655, 236660, 23666 236780, 236710,	5, 236760, 236765,		085843
Pedestal for # 236655, 236660, 236665, 2 236780, 236710,	36760, 236765,		085842
Recommended faucets			
	je, Projection 113		



## **D-Neo Washbasin** # 2366650000 / 2366650060

|< 650 mm >|

Single lever basin mixer M ceramic cartridge, Projection 139 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	B11020001
Single lever basin mixer M ceramic cartridge, Projection 139 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	B21020001
Single lever basin mixer for concealed installation normal spray, ceramic cartridge, aerator adjustable, connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 1 - 5 bar, Projection 174 mm,	C11070003
Single lever basin mixer M ceramic cartridge, Projection 139 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	B11020002
Single lever basin mixer for concealed installation normal spray, ceramic cartridge, aerator adjustable, connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 1 - 5 bar, Projection 225 mm,	C11070004
Single lever basin mixer M ceramic cartridge, Projection 139 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	B21020002
Single lever basin mixer M ceramic cartridge, projection 107 mm, flexible connection hoses 3/8", normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	A11020001
Single lever basin mixer M ceramic cartridge, projection 107 mm, flexible connection hoses 3/8", normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	A11020002
Single lever basin mixer M ceramic cartridge, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	DE1020001
Single lever basin mixer M ceramic cartridge, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	DE1020002
Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, with pop-up waste set,	DE1021001



## **D-Neo Washbasin** # 2366650000 / 2366650060

|< 650 mm >|

Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 1 - 5 bar, without pop-up waste set,	DE1021002
Single lever basin mixer M ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 1 - 5 bar, with pop-up waste set,	N11020001
Single lever basin mixer M ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 1 - 5 bar, without pop-up waste set,	N11020002
Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 1 - 5 bar, with pop-up waste set,	N11021001
Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 1 - 5 bar, without pop-up waste set,	N11021002
Single lever basin mixer M MinusFlow ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 3,5 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 1 - 5 bar, with popup waste set,	N11022001
Single lever basin mixer M MinusFlow ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 3,5 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 1 - 5 bar, without pop-up waste set,	N11022002
Single lever basin mixer M ceramic cartridge, projection 116 mm, aerator with Easy-clean sprayplate, normal spray, connection size DN15, recommended operating pressure 1 - 5 bar, without pop-up waste set,	CE1020002
Single lever basin mixer M ceramic cartridge, projection 116 mm, aerator with Easy-clean sprayplate, normal spray, connection size DN15, recommended operating pressure 1 - 5 bar, with pop-up waste set,	CE1020001
Single lever basin mixer for concealed installation normal spray, ceramic cartridge, aerator with Easy-clean sprayplate, connection type: basic set for concealed installation, recommended operating pressure 1 - 5 bar, Projection 200 mm,	CE1070004
Single lever basin mixer M ceramic cartridge, projection 122 mm, aerator with Easy-clean sprayplate, flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, recommended operating pressure 1 - 5 bar, with pop-up waste set,	WA1020001
Single lever basin mixer M ceramic cartridge, projection 122 mm, aerator with Easy-clean sprayplate, flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, recommended operating pressure 1 - 5 bar, without pop-up waste set,	WA1020002



## **D-Neo Washbasin** # 2366650000 / 2366650060

|< 650 mm >|

Circle Love having action for a small disability in a small	
Single lever basin mixer for concealed installation normal spray, ceramic cartridge, aerator with Easy-clean sprayplate, flow rate 5,0 l/min (3 bar), connection type: basic set for concealed installation, includes: visible parts, recommended operating pressure 1 - 5 bar, projection 202 mm,	WA1070004
Single lever basin mixer M ceramic cartridge, projection 129 mm, aerator with Easy-clean sprayplate, flow rate 5,0 l/min (3 bar), normal spray, recommended operating pressure 1 - 5 bar, with pop-up waste set,	MH1020001
Single lever basin mixer M ceramic cartridge, projection 129 mm, aerator with Easy-clean sprayplate, flow rate 5,0 l/min (3 bar), normal spray, recommended operating pressure 1 - 5 bar, without pop-up waste set,	MH1020002
Single lever basin mixer for concealed installation normal spray, ceramic cartridge, aerator with Easy-clean sprayplate, flow rate 5,0 l/min (3 bar), connection type: basic set for concealed installation, recommended operating pressure 1 - 5 bar,	MH1070004
Single lever basin mixer M FreshStart connection size DN15,	WA1021001
Single lever basin mixer M FreshStart connection size DN15,	WA1021002
Single lever basin mixer M MinusFlow connection size DN15,	WA1022001
Single lever basin mixer M MinusFlow connection size DN15,	WA1022002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.